



## System 75 - Chemical resistant (PP)

All components RoHS-compatible.

### Design:

- Extraction arm for mounting on table
- Working range 550 - 1620 mm
- Recommended airflow 80 to 180 m<sup>3</sup>/h
- Diameter of tube Ø75 mm
- Tubes made of chemical resistant polypropylene (PP)
- Joints made of shatterproof, chemical resistant polypropylene (PP)
- Colour of joints: white (-5) or red (-4)
- All O-rings maintenance free
- Integrated valve. When in an open position out of the flow path to maintain the maximum amount of flow
- All threaded stays, springs and thumbscrews made of acid-proof stainless steel (AISI 316L)
- All rivets made of chemical resistant polypropylene (PP) for increased durability in aggressive environments
- All hoods can be provided with a protective netting (accessory) to reduce the risk of extracting foreign objects
- Dismantling of the arm without tools for cleaning




Links: [Pressure drop chart](#), [Mounting](#), [User's manual](#), [Capture efficiency](#), [Material compatibility](#)

## Working area

We do not recommend a stationary working position in the upper or lower working area.

All units in mm



- A: Model 75-35-1-7-5
- B: Model 75-45-1-7-5
- C: Model 75-55-1-7-5
- D: Model 75-3535-1-7-5
- E: Model 75-5545-1-7-5
- F: Model 75-6555-1-7-5
- G: Model 75-9065-1-7-5