



## System 100 – Chemical resistant (PP)

All components RoHS-compatible.

### Design:

- Extraction arm for mounting on wall and ceiling
- Working range 795 - 2630 mm
- Recommended airflow 140 to 400 m<sup>3</sup>/h
- Diameter of tube Ø100 mm
- POP<sup>®</sup> rivets made of acid-proof stainless steel (AISI 316L) for increased durability in aggressive environments
- Tubes and joints made of chemical resistant polypropylene (PP)
- Colour of joints: white
- All O-rings maintenance free
- Integrated valve. When in an open position out of the flow path to maintain the maximum amount of flow
- All threaded stays, springs and thumbscrews made of acid-proof stainless steel (AISI 316L)
- All hoods can be provided with a protective netting (accessory) to reduce the risk of extracting foreign objects
- Dismantling of the arm without tools for cleaning



Links: [Pressure drop chart](#), [Mounting without gas spring](#), [Mounting with gas springs](#), [User's manual](#)  
[Capture efficiency](#),

## Working area

*We do not recommend a stationary working position in the upper or lower working area.*

*All units in mm*

*\* With 1 gas spring*

*\*\* With 2 gas springs*

A: Model 100-55-3-7-5  
B: Model 100-4540-3-7-5  
C: Model 100-5545-3-7-5  
D: Model 100-6555-3-7-5  
E: Model 100-9065-3-7-5\*  
F: Model 100-10585-3-7-5\*\*  
G: Model 100-135105-3-7-5\*\*

